



Eaton Metered Input rack PDU, 0U, 42U, Input IEC-60309 16A 3ph, 11 kW max, 16A, 346-415V, Outlets 36XC13 : 6XC19



Catalog No. EMIB00

Similar to illustration

Delivery program

Fitted With:	Display Mounting material Ampere Meter
Type	Rack PDU
Input Connection	IEC-60309 16A 3ph
Cord Length	3m
Input Voltage	346-415V
Phase	Three-phase
Frequency Rating	50/60 Hz
Ethernet Interface	Yes
Serial Interface	Yes
Form Factor	0U (Vertical)
Outlet Control	No
Operating Temperature	0° to 60°C (32° to 140°F)
Outlets	36XC13 : 6XC19
Number of Outputs C13	36
Number of Outputs C19	6
Amperage Rating	16A
Mounting Direction	Vertical
ETIM Class	EC002762
Electrical Connection	Connecting cord with plug
Evaluation	At distance
Mounting Dimension (metrical)	52
Mounting Dimension (standardised)	Metric
Switchable	No
Over Voltage Category	2
Wattage	11 kW max
Communication	HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
SNMP	Yes
Mass Configuration	Yes
Package Contents	PDU, Mounting accessories, Network cable, Configuration cable, Splitter for daisy-chaining, Quickstart guide, Safety Instructions
Number of Outputs C20	0
Num of Outputs PC (SCHUKO)	0
Number of Outputs (Other)	0
Number of Outlets with Earth Pin	42
Color	Black

Technical data ETIM 7.0

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)		
Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ec1@ss10.0.1-27-14-26-90 [AKN612013])		
Mounting dimension (standardised)		Metric
Mounting dimension	mm	52
Mounting direction		Vertical
Electrical connection		Connecting cord with plug
Type of electric connection		Other
Cable length	m	3
Number of socket outlets with protective contact		0
Number of socket outlets with earth pin		42
Number of C13 socket outlets		36
Number of C19 socket outlets		6
Number of C20 socket outlets		0
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		0
Number of height units		0
Length	mm	1,829
Width	mm	53
Height	mm	52
Depth	mm	1,829
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		No
SNMP		Yes
With display		Yes
Evaluation		At distance
With LED indication		No
With fuse		No
Ampere meter		Yes
With temperature measurement		No
With mounting material		Yes