



**Eaton Metered Input rack PDU, 2U, Input IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 12XC13 : 4XC19**



**Catalog No. EMIH06**

Similar to illustration

## Delivery program

Type		Rack PDU
Input Connection		IEC-60309 32A 1Ph
Cord Length		3m
Input Voltage		200-240V
Phase		Single-phase
Frequency Rating		50/60 Hz
Ethernet Interface		Yes
Serial Interface		Yes
Form Factor		2U
Outlet Control		No
Operating Temperature		0° to 60°C (32° to 140°F)
Outlets		12XC13 : 4XC19
Number of Outputs C13		12
Number of Outputs C19		4
Amperage Rating		32A
Mounting Direction		Horizontal
ETIM Class		EC002762
Fitted With:		Display Ampere Meter Mounting material
Electrical Connection		Connecting cord with plug
Evaluation		At distance
Mounting Dimension (metrical)		444.5
Mounting Dimension (standardised)		482.6 mm (19 inch)
Switchable		No
Over Voltage Category		2
Wattage		7.4 kW max
Communication		HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
SNMP		Yes
Mass Configuration		Yes
Package Contents		PDU mounting accessories network cable configuration cable splitter for daisy-chaining Quickstart Safety Instructions
Number of Outputs C20		0
Num of Outputs PC (SCHUKO)		0
Number of Outputs (Other)		0

Number of Outlets with Earth Pin		16
Circuit Breaker		(2) single-pole
Color		Black

## Technical data ETIM 7.0

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)		
Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ecl@ss10.0.1-27-14-26-90 [AKN612013])		
Mounting dimension (standardised)		482.6 mm (19 inch)
Mounting dimension	mm	444.5
Mounting direction		Horizontal
Electrical connection		Connecting cord with plug
Type of electric connection		Other
Cable length	m	3
Number of socket outlets with protective contact		0
Number of socket outlets with earth pin		16
Number of C13 socket outlets		12
Number of C19 socket outlets		4
Number of C20 socket outlets		0
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		0
Number of height units		2
Length	mm	127
Width	mm	87.2
Height	mm	444.5
Depth	mm	127
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		No
SNMP		Yes
With display		Yes
Evaluation		At distance
With LED indication		No
With fuse		No
Ampere meter		Yes
With temperature measurement		No
With mounting material		Yes