

Panel PC

**Part no. XP-504-BOXPC-A10-A00-2B
EP-400011**

Product name	Eaton XP Panel PC
Part no.	XP-504-BOXPC-A10-A00-2B
EAN	7640130099999
Product Length/Depth	55 millimetre
Product height	170 millimetre
Product width	92.3 millimetre
Product weight	1.15 kilogram
Certifications	CE
Product Tradename	XP
Product Type	Panel PC
Product Sub Type	None
Globally Marketable	Yes
Features	Customer individual configuration
Fitted with:	Other storage media
Degree of protection	NEMA 1 IP20
Degree of protection (front side)	IP20
Mounting method	Rail mounting possible Wall mounting/direct mounting
Protocol	EtherNet/IP
Voltage type	DC
Operating temperature - min	0 °C
Operating temperature - max	45 °C
Supply voltage at AC, 50 Hz - min	0
Supply voltage at AC, 50 Hz - max	0
Supply voltage at DC - min	20
Supply voltage at DC - max	28
Operating system	Windows 10

Technical data ETIM 8.0

Programmable logic controllers PLC (EG000024) / Industrial PC (EC001413)		
Information, communication and media technology / Computer system for industrial use / Industrial PC / Industrial PC (built-in) (ecl@ss10.0.1-19-20-01-02 [ACM011012])		
Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	20 - 28
Voltage type of supply voltage		DC
Number of HW-interfaces industrial Ethernet		2
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		1
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		0
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		4
Number of HW-interfaces parallel		0

Number of HW-interfaces Wireless			0
Number of HW-interfaces other			0
Supporting protocol for PROFIBUS			No
Supporting protocol for CAN			No
Supporting protocol for INTERBUS			No
Supporting protocol for ASI			No
Supporting protocol for KNX			No
Supporting protocol for Modbus			No
Supporting protocol for Data-Highway			No
Supporting protocol for DeviceNet			No
Supporting protocol for SUCONET			No
Supporting protocol for LON			No
Supporting protocol for PROFINET IO			No
Supporting protocol for PROFINET CBA			No
Supporting protocol for SERCOS			No
Supporting protocol for Foundation Fieldbus			No
Supporting protocol for EtherNet/IP			Yes
Supporting protocol for AS-Interface Safety at Work			No
Supporting protocol for DeviceNet Safety			No
Supporting protocol for INTERBUS-Safety			No
Supporting protocol for PROFIsafe			No
Supporting protocol for SafetyBUS p			No
Supporting protocol for other bus systems			No
Radio standard Bluetooth			No
Radio standard Wi-Fi 802.11			No
Radio standard GPRS			No
Radio standard GSM			No
Radio standard UMTS			No
IO link master			No
Suitable for operating system Windows 9x			No
Suitable for operating system Windows 2000			No
Suitable for operating system Windows XP			No
Suitable for operating system Windows ME			No
Suitable for operating system Windows CE			No
Suitable for operating system Linux			No
Suitable for operating system Windows Vista			No
Suitable for operating system Windows 2003 Server			No
Suitable for operating system Windows 7			No
Suitable for operating system Windows 8			No
Suitable for other operating system			No
Preinstalled operating system			
Max. main memory		MB	8
Degree of protection (IP)			IP20
Degree of protection (NEMA)			1
Operating temperature		°C	0 - 45
Construction type housing			Box
With hard disc			No
Processor type			Intel Atom
Processor clock rate		GHz	2
With graphic card			No
With sound card			No
With optical drive			No
With floppy disc drive			No
Number of free AGP-slots			0
Number of free PCI-slots			0

With other storage media			Yes
Number of free ISA-slots			0
Number of free PCMCIA-slots			0
Number of other free slots			0
Rail mounting possible			Yes
Wall mounting/direct mounting			Yes
Front built-in possible			No
Rack-assembly possible			No
Number of storage media bays			1
Suitable for safety functions			No
Width		mm	92.3
Height		mm	170
Depth		mm	55
Memory capacity hard disc		TB	0.064