

Panel PC

**Part no. XP-504-21-TERMINAL
EP-400139**

Product name	Eaton XP Panel PC
Part no.	XP-504-21-TERMINAL
EAN	7640130099951
Product Length/Depth	544 millimetre
Product height	335.5 millimetre
Product width	75 millimetre
Product weight	5.9 kilogram
Certifications	CE
Product Tradename	XP
Product Type	Panel PC
Product Sub Type	None
Globally Marketable	Yes
Features	Customer individual configuration
Fitted with:	Touch screen
Degree of protection	NEMA 12 IP65
Degree of protection (front side)	IP65
Mounting method	Front build in possible
Voltage type	DC
Operating temperature - min	0 °C
Operating temperature - max	45 °C
Supply voltage at AC, 50 Hz - min	0
Supply voltage at AC, 50 Hz - max	0
Supply voltage at DC - min	20
Supply voltage at DC - max	28
Display type	TFT
Screen size (diagonal)	21.5 in

Technical data ETIM 8.0

Programmable logic controllers PLC (EG000024) / Industrial PC (EC001413)		
Information, communication and media technology / Computer system for industrial use / Industrial PC / Industrial PC (built-in) (ecl@ss10.0.1-19-20-01-02 [ACM011012])		
Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	20 - 28
Voltage type of supply voltage		DC
Number of HW-interfaces industrial Ethernet		0
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		0
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		0
Number of HW-interfaces parallel		0

Number of HW-interfaces Wireless		0
Number of HW-interfaces other		0
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		No
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		No
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		No
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		No
Radio standard Bluetooth		No
Radio standard Wi-Fi 802.11		No
Radio standard GPRS		No
Radio standard GSM		No
Radio standard UMTS		No
IO link master		No
Suitable for operating system Windows 9x		No
Suitable for operating system Windows 2000		No
Suitable for operating system Windows XP		No
Suitable for operating system Windows ME		No
Suitable for operating system Windows CE		No
Suitable for operating system Linux		No
Suitable for operating system Windows Vista		No
Suitable for operating system Windows 2003 Server		No
Suitable for operating system Windows 7		No
Suitable for operating system Windows 8		No
Suitable for other operating system		No
Preinstalled operating system		None
Max. main memory	MB	0
Degree of protection (IP)		IP65
Degree of protection (NEMA)		12
Operating temperature	°C	0 - 45
Construction type housing		Other
With hard disc		No
Processor type		Other
Processor clock rate	GHz	0
With graphic card		No
With sound card		No
With optical drive		No
With floppy disc drive		No
Number of free AGP-slots		0
Number of free PCI-slots		0

With other storage media			No
Number of free ISA-slots			0
Number of free PCMCIA-slots			0
Number of other free slots			0
Rail mounting possible			No
Wall mounting/direct mounting			No
Front built-in possible			Yes
Rack-assembly possible			No
Number of storage media bays			0
Suitable for safety functions			No
Width		mm	75
Height		mm	335.5
Depth		mm	544
Memory capacity hard disc		TB	0