



Fuse-link, low voltage, AC 415 V, BS88/F2, 21 x 68 mm, gM, BS

ESD63M100

Similar to illustration

| | |
|----------------------|---------------------------------------------------------|
| Product name | Eaton Bussmann series low voltage British standard fuse |
| Part no. | ESD63M100 |
| EAN | 5027590498708 |
| Product Length/Depth | 67 millimetre |
| Product height | 22 millimetre |
| Product width | 22 millimetre |
| Product weight | 42.1 gram |
| Compliances | Contact Manufacturer |
| Product Tradename | None |
| Product Type | Low voltage British standard fuse |
| Product Sub Type | None |
| Amperage Rating | 63 A |
| Voltage rating | 415 V |
| Voltage type | AC |
| Breaking capacity | 80 kA |
| Class | Class gM |
| Application | general industrial applications |
| Fuse type | ESD |
| Fuse size | BS88/F2 |
| Fitted with: | Offset bladed tags |
| Connection | Blade end |
| Suitable for | 63ENS Safelec fuse holder SC63 Safeclip fuse holder |

Technical data ETIM 8.0

| | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|-----------------------|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) | | |
| Fuse construction type according to IEC 60269 | | F2 |
| Type of current | | AC |
| Rated voltage AC | V | 415 |
| Rated voltage DC | V | |
| Rated current | A | 63 |
| Utilization category | | gM (motor protection) |
| Breaking capacity | kA | 80 |
| Colour code | | None |
| Type of fuse status indicator | | None |
| Power loss at rated current | W | 2.5 |
| Mounting holes | | |
| Centre-to-centre distance of connections | mm | |