

FG630

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		FG630
EAN		5027590019972
Product Length/Depth		263 millimetre
Product height		74 millimetre
Product width		74 millimetre
Product weight		1275 gram
Compliances		RoHS Compliant
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		630 A
Voltage rating		415 V
Voltage type		AC/DC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		FG
Fitted with:		Centre bolted tags
Connection		167/231 mm fixing centre

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ec1@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	415
Rated voltage DC	V	400
Rated current	A	630
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	50
Mounting holes		M10
Centre-to-centre distance of connections	mm	231