

FWH-.250A6F

Similar to illustration

| | | |
|-----------------------------|--|--|
| Product name | | Eaton Bussmann series high speed cylindrical fuse |
| Part no. | | FWH-.250A6F |
| EAN | | 5027590499439 |
| Product Length/Depth | | 33 millimetre |
| Product height | | 7 millimetre |
| Product width | | 7 millimetre |
| Product weight | | 2.8 gram |
| Compliances | | RoHS Compliant CE Marked |
| Certifications | | CSA Certified UL Recognized |
| Product Tradename | | None |
| Product Type | | High speed cylindrical fuse |
| Product Sub Type | | None |
| Amperage Rating | | 0.25 A |
| Voltage rating | | 700 V |
| Voltage type | | AC/DC |
| Interrupt rating | | 50 kAIC |
| Class | | Class aR |
| Clearing (I ₂ T) | | 0.05 at 500 V |
| Application | | Semiconductor, DC Common bus, DC drives, Power converters/rectifiers |
| Fuse indicator | | Other |

Technical data ETIM 8.0

| | | |
|---|----|---|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015]) | | |
| Model | | Ceramic fuse |
| Size | | Other |
| Voltage type | | AC/DC |
| Rated current | A | 0.25 |
| Rated voltage | V | 500 |
| Utilization category | | aR (accompanied semiconductor protection) |
| Rated operating frequency | Hz | 45 - 62 |
| Type of fuse status indicator | | Other |
| Release characteristic | | Other |
| Breaking capacity | kA | 50 |
| Power loss at rated current | W | 2.7 |