



Part no.  
Article no.

**BUSS ONE TIME FUSE**  
**NOS-30**

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	30
Rated voltage			AC 600 V
Construction size			UL Class K5
Size			20.6 x 127
Breaking Capacity		kA	50
usable for size/applications			Light duty circuit locations
Standard/Approval			UL
Shape			cylindrical
Standards/Regulations			UL Listed

### Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			Other
Nominal rated current		A	30
Nominal rated voltage		V	600
Utilization category			Other
Type of fuse status indicator			None

### Additional product information (links)

Product Data Sheet (pdf)	<a href="http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1030_NON_NOS.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1030_NON_NOS.pdf</a>
--------------------------	---