



Fuse-link, low voltage, AC 415 V, BS88/F2, 14 x 59 mm, gM, BS

NSD32M36

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		36A 415V M/S FUSE
EAN		5027590504898
Product Length/Depth		59 millimetre
Product height		18 millimetre
Product width		18 millimetre
Product weight		16.2 gram
Compliances		RoHS Compliant CE Marked
Certifications		BS88 IEC 60269-2
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		6 A
Voltage rating		415 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gM
Application		general industrial applications
Fuse type		NSD
Fitted with:		Offset bladed tags
Connection		Blade end
Suitable for		32NNS Safeloc fuse holder SC32 Safeclip fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		F2
Type of current		AC
Rated voltage AC	V	415
Rated voltage DC	V	
Rated current	A	6
Utilization category		gM (motor protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	2.4
Mounting holes		
Centre-to-centre distance of connections	mm	