



Fuse-link, low voltage, 500 A, AC 660 V, DC 450 V, BS88/C2, 74 x 210 mm, gL/gG, BS

**TTM500**

Product name	Eaton Bussmann series low voltage British standard fuse	
Part no.	TTM500	
EAN	5996516026694	
Product Length/Depth	210 millimetre	
Product height	75 millimetre	
Product width	75 millimetre	
Product weight	1074 gram	
Compliances	CE Marked RoHS Compliant	
Certifications	BS88 KEMA IEC 60269 EAC	
Product Tradename	None	
Product Type	Low voltage British standard fuse	
Product Sub Type	None	
Amperage Rating	500 A	
Voltage rating	660 V	
Voltage type	AC/DC	
Breaking capacity	80 kA	
Class	Class gG/gL	
Application	general industrial applications	
Fuse type	TTM	
Fuse size	BS88/C2	
Fitted with:	Centre bolted tags	
Connection	133/184 mm fixing centre	

**Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		C2
Type of current		AC/DC
Rated voltage AC	V	660
Rated voltage DC	V	450
Rated current	A	500
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	
Mounting holes		M10
Centre-to-centre distance of connections	mm	183.8