



Fuse-link, low voltage, 50 A, AC 480 V, DC 300 V, 11 x 57 mm, class G, UL, CSA, time-delay

Catalog No. **SC-50**

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	50
Rated voltage			AC 480 V DC 300 V
Size			57.1 x 10.4 mm
Utilization category			G
Description			rejection-type
Breaking Capacity		kA	100
usable for size/applications			fusible branch panelboards, HVAC branch circuit protection
Release characteristic	class		time-delay
Standard/Approval			UL CSA
Shape			cylindrical
Standards/Regulations			UL 248-5
Time delay			time-delay 12 seconds (minimum) at 200% of rated current

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			Other
Rated voltage		V	480 - 480
Rated voltage			Other
Voltage type			AC
Utilization category			Other
Rated operating frequency		Hz	45 - 62
Nominal current		A	50
With striker			No
Release characteristic			G
Breaking capacity		kA	100

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1024_SC.pdf
Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/supplemental/sc.html