



Representative Image

Ref. No. 102617 | Cat. No. MC1A310AT1
Description: Screw terminal 3P, AC3 4kW, 24V/50-60Hz AC Bifreq. Coil, 1NO (GE)
EAN 8425095026179
Home > Power devices > Contactors > Series M - Compact contactor series up to 12A

- Control circuit:
Alternating current up to 600V
Direct current up to 250V
- Terminal numbering in accordance with EN 50012
- Fixing by clipping onto 35mm DIN rail (EN 50022) or by screws
- Degree of protection IP20 in accordance with EN 60529
- Printed circuit version available
- Screws and fast-on terminals protected against accidental contact in accordance with VDE 0106 T.100 and VBG4
- Facility to mount instant and timed auxiliary contact blocks and voltage suppressor block
- Conform to IEC/EN60947-1, IEC/EN60947-4-1, IEC/EN60947-5-1

Descriptors

Category	Series M - Compact contactor series up to 12A
----------	---

Specifications

Series	Three-pole contactors 6, 9 and 12 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Control Voltage: AC	24 V
Terminal	Screw terminal
Aux Contacts	1NO
Motors = 440V, 3-phase 50/60Hz AC3	9 A
Package (pcs)	20

Classifications

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

Dimensions

Weight	0.170 kg
--------	----------

Publications

Title	Publication No.	Publication Type
4-pole - Auxiliary contactor MC1A-MCRA (pdf)		
4-pole - Auxiliary contactor MC1A-MCRA (3DPDF format)	3D-00066-PDF	Drawings - CAD - 3D
4-pole - Auxiliary contactor MC1A-MCRA (stp)		
4-pole - Auxiliary contactor MC1A-MCRA (STEP format)	3D-00066	Drawings - CAD - 3D

Additional Documentation: Visit our Publication Library to find technical documentation, specifications, articles, promotional literature, 3D's,...