



Category

Ref. No. 102622 | Cat. No. MC1A310AT6

Description: Screw terminal 3P, AC3 4kW, 230V/50-60Hz AC Bifreq. Coil, 1NO (GE)

EAN 8425095026223

Home > Power devices > Contactors > Series M - Compact contactor series up to 12A

• Control circuit: Alternating current up to 600V Direct current up to 250V

- Terminal numbering in accordance with EN 50012
- Fixing by clipping onto 35mm DIN rail (EN 50022) or by screws
 Degree of protection IP20 in accordance with EN 60529
- Printed circuit version available
- Screws and fast-on terminals protected against accidental contact in accordance with VDE 0106 T.100 and VBG4

Series M - Compact contactor series up to 12A

- Facility to mount instant and timed auxiliary contact blocks and voltage suppressor block
 Conform to IEC/EN60947-1, IEC/EN60947-4-1, IEC/EN60947-5-1

Descriptors			

Specifications						
Series	Three-pole contactors 6, 9 and 12 A (AC3)					
Control circuit	AC					
Frequency Control Voltage: AC	50-60 Hz					
Control Voltage: AC	220-230 V					
Terminal	Screw terminal					
Aux Contacts	1NO					
Motors = 440V, 3-phase 50/60Hz AC3	9 A					
Package (pcs)	20					

Classifications							
ETIM 5.0	EC000066 - Power contactor, AC switching						
ETIM 6.0	EC000066 - Power contactor, AC switching						
ETIM 7.0	EC000066 - Power contactor, AC switching						

Dimensions	
Weight	0.170 kg



Publications						
Title	Publication No.	Publication Type				
4-pole - Auxiliary contactor MC1A-MCRA (pdf)						
4-pole - Auxiliary contactor MC1A-MCRA (3DPDF format)	3D-00066-PDF	Drawings - CAD - 3D				
4-pole - Auxiliary contactor MC1A-MCRA (stp)						
4-pole - Auxiliary contactor MC1A-MCRA (STEP format)	3D-00066	Drawings - CAD - 3D				

Additional Documentation: Visit our Publication Library to find technical documentation, specifications, articles, promotional literature, 3D's,...