



Representative Image

Ref. No. 104063 | Cat. No. CL00A301TJ
Description: CL00A301TJ Contactor 3-pole 110V 50Hz AC
EAN 8017018040630
Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 110V 50Hz AC Max.oper.current AC1 (A):25 Max.oper.current AC3 (A):9 Admissible power 220V/230V (kW):2.2 Admissible power 380V/400V (kW):4 Aux.contacts:1NC

Descriptors

Category	Series CL - Contactor series for General Purpose application
----------	--

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	60 Hz 50-60 Hz
Range	CL Contactors
Terminal type	Screw terminal
Non-inductive loads AC1	25 A
Motors = 440V, 3-phase 50/60Hz AC3	9 A
Electrical endurance: # operations AC3	2 x 10 ⁶
Aux Contacts	1NC
Power contacts	3NO
Control Voltage: AC	110 V
Admissible power AC3 220V, 230V	2.2 kW
Admissible power AC3 380V, 400V	4 kW
Admissible power AC3 415V, 440V	4 kW
Admissible power AC3 500V	5.5 kW

Classifications

ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

Dimensions

Weight	0,28 kg
--------	---------

Publications

Title	Publication No.	Publication Type
CONACL00F CONACL00 Front view	CONACL00F	Commercial Drawings
CONACL00R CONACL00 Rear view	CONACL00R	Commercial Drawings
CONACL00T CONACL00 Total view	CONACL00T	Commercial Drawings
CONACL00L CONACL00 Side view	CONACL00L	Commercial Drawings

Additional Documentation: Visit our Publication Library to find technical documentation, specifications, articles, promotional literature, 3D's,...