



Representative Image

**Ref. No. 104413 | Cat. No. CL04AB00MJ**
**Description: CL04AB00MJ Contactor 4-pole (2:2) 110V 50Hz AC 50Hz**
**EAN 8425095044135**
**Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application**

Series CL &amp; RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 110V 50Hz AC Max.oper.current AC1 (A):60 Admissible power 220V/230V (kW):9 Admissible power 380V/400V (kW):16

**Descriptors**

Category	Series CL - Contactor series for General Purpose application
----------	--

**Specifications**

Series	Four-pole contactors from 12 to 80 A (AC3) [2NO+2NC]
Control circuit	AC
Frequency Control Voltage: AC	60 Hz 50-60 Hz
Range	CL Contactors
Terminal type	Double clamp terminal
Non-inductive loads AC1	60 A
Electrical endurance: # operations AC1	1.5 x 10 <sup>6</sup>
Control Voltage: AC	110 V
Admissible power AC3 220V, 230V	9 kW
Admissible power AC3 380V, 400V	16 kW
Admissible power AC3 415V, 440V	16 kW
Admissible power AC3 500V	18.5 kW

**Classifications**

ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching