



Representative Image

Ref. No. 104433 | Cat. No. CL07AB00MJ
Description: CL07AB00MJ Contactor 4-pole (2:2) 110V 50Hz AC 50Hz
EAN 8425095044333
Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 110V 50Hz AC Max.oper.current AC1 (A):110 Admissible power 220V/230V (kW):18.5 Admissible power 380V/400V (kW):30

Descriptors

Category	Series CL - Contactor series for General Purpose application
----------	--

Specifications

Series	Four-pole contactors from 12 to 80 A (AC3) [2NO+2NC]
Control circuit	AC
Frequency Control Voltage: AC	60 Hz 50-60 Hz
Range	CL Contactors
Terminal type	Double clamp terminal
Non-inductive loads AC1	110 A
Electrical endurance: # operations AC1	1.8 x 10 ⁶
Control Voltage: AC	110 V
Admissible power AC3 220V, 230V	18.5 kW
Admissible power AC3 380V, 400V	30 kW
Admissible power AC3 415V, 440V	37 kW
Admissible power AC3 500V	40 kW

Classifications

ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching