


Ref. No. 113470 | Cat. No. CL10E300MWH
Description: CL10E300MWH Contactor 3-pole 60-72V 50Hz / 60Hz AC
EAN 8425095134706
Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V):60-72V 50Hz/60Hz DC +/-30%
 Max.oper.current AC1 (A):140Max.oper.current AC3 (A):105 Admissible power 220V/230V (kW):30 Admissible power 380V/400V (kW):55



Representative Image

Descriptors

Category	Series CL - Contactor series for General Purpose application
----------	--

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC/DC
Range	CL Contactors
Terminal type	Double clamp terminal
Non-inductive loads AC1	140 A
Motors = 440V, 3-phase 50/60Hz AC3	105 A
Electrical endurance: # operations AC3	1.5 x 10 ⁶
Power contacts	3NO
Admissible power AC3 220V, 230V	30 kW
Admissible power AC3 380V, 400V	55 kW
Admissible power AC3 415V, 440V	55 kW
Admissible power AC3 500V	65 kW

Classifications

ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

Dimensions

Weight	1,46 kg
--------	---------