

Ref. No. 783520 | Cat. No. DMA63NC20/030
Description: RCBO Residual current circuit breaker with overcurrent protection DMA type A 3P+N C 20A 30mA 6kA
EAN 3390207835206
Home > Modular DIN-rail devices > People protection > People protection


Representative Image

Descriptors

Category	People protection
----------	-------------------

Specifications

Series	Residual current circuit breaker with overcurrent protection
Range	DMA63N
Type	Type A
Un	400 Vac
Poles	3P+N
Rated current In	20 A
Residual current	30 mA
Operating time	Instantaneous
AC/DC	AC
Number of modules	4
Switching off capacity	C (5-10 In)
Terminal capacity flexible/rigid cable	Top terminal: 1-25 mm ² /Bottom terminal: 1-35 mm ²
Tropicalisation according to IEC 60068-2-28/2-30	95%RV at 55°C
Electrical service life	10000
Selectivity class	3
Minimum servicevoltage	195 V
Frequency	50/60 Hz
Storage temperature	-25°C / +40°C
Dielectric strength	2500 V
Shock voltage	6
Protection Degree	IP20
Nuisance tripping resistance	250 A 8/20μs - 200 A 0.5 μs - 100 kHz
Differential making and breaking capacity	I(Δ)m = 3000 A

Classifications

Approvals	CE IMQ
Approval/norm	EN/IEC 61009-1

Classifications

ETIM 5.0	EC000003 - Residual current circuit breaker (RCCB)
ETIM 6.0	EC000003 - Residual current circuit breaker (RCCB)
ETIM 7.0	EC000905 - Earth leakage circuit breaker

Dimensions

Weight	0.480 kg
--------	----------

Package Information

Standard packing	1
------------------	---

Operating Performance

Operating temperature	-5 / +60°C
-----------------------	------------