

Extension- and compensating cables, multi-paired

PVC insulated - with and without steel wire armouring or foil screen

Extension and compensating cables, multi-paired version - suitable for use in temperature measurement and manufacturing process control

Info

Version SY - Armoured against mechanical loads

Version ST - Screened against electromagnetic interference



Product Make-up

Version Y:

- Fine-wire conductor alloy
- PVC core insulation
- Cores twisted into layers
- PVC outer sheath

Version SY:

- Design as version Y
- Additional galvanised steel wire braiding
- PVC outer sheath

Version ST:

- Design as version Y
- Cores twisted in pairs, pairs twisted in layers
- Aluminium foil screening + drain wire
- PVC outer sheath

Design, for example PVC-PVC-S-PVC:

- PVC core insulation
- PVC inner sheath
- Steel wire braiding
- PVC outer sheath

Design, for example PVC-ST-PVC:

- PVC core insulation
- Static foil screen
- PVC outer sheath

Colour identity code

DIN 43710

Negative conductor and outer sheath:

Fe/CuNi: blue

NiCr/Ni: green

Last Update (25.11.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

Extension- and compensating cables, multi-paired

PtRh/Pt: white
Positive conductor: always red
IEC 60 584
Positive conductor and outer sheath:
Fe/CuNi: black
NiCr/Ni: green
PtRh/Pt: orange
Negative conductor: always white
Extension-conductor alloys are identified
with X, e.g. JX (Fe/CuNi)
Compensating-conductor alloys are
identified with C, e.g. KCA (NiCr/Ni)

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000838 ETIM 5.0 Class-Description: Thermocouple cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000838 ETIM 6.0 Class-Description: Thermocouple cable
Core identification code:	From 4 cores in pairs with consecutively marked numbers (1-1, 2-2, 3-3, 4-4...)
Based on:	Limiting deviation in accordance with DIN and IEC in accordance with class 2
Conductor stranding:	48 x 0.20 mm
Minimum bending radius:	For flexible use: 12.5 x outer diameter Type SY with steel braid: 15 x outer diameter Type ST with foil screen: 15 x outer diameter
Temperature range:	(referring to insulation and sheath material) Flexing: -5° C to +80° C Fixed installation: -40° C to +80° C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Extension- and compensating cables, multi-paired

Article number	Thermocouple	Product Make-up	Cable design	Number of cores and mm ² per conductor	Outer diameter [mm]	Weight (kg/km)
Type Y without steel wire braiding						
0155001	Fe/CuNi	DIN-LX	PVC-PVC	4 x 1.5	8.2	130
0165001	Fe/CuNi	IEC-JX	PVC-PVC	4 x 1.5	8.2	130
0156001	NiCr/Ni	DIN-KCA	PVC-PVC	4 x 1.5	8.2	130
0166001	NiCr/Ni	IEC-KCA	PVC-PVC	4 x 1.5	8.2	130
0157001	PtRh/Pt	DIN-RCB/SCB	PVC-PVC	4 x 1.5	8.2	130
0167001	PtRh/Pt	IEC-RCB/SCB	PVC-PVC	4 x 1.5	8.2	130
0155002	Fe/CuNi	DIN-LX	PVC-PVC	6 x 1.5	10.2	200
0165002	Fe/CuNi	IEC-JX	PVC-PVC	6 x 1.5	10.2	200
0156002	NiCr/Ni	DIN-KCA	PVC-PVC	6 x 1.5	10.2	200
0166002	NiCr/Ni	IEC-KCA	PVC-PVC	6 x 1.5	10.2	200
0157002	PtRh/Pt	DIN-RCB/SCB	PVC-PVC	6 x 1.5	10.2	200
0167002	PtRh/Pt	IEC-RCB/SCB	PVC-PVC	6 x 1.5	10.2	200
0155003	Fe/CuNi	DIN-LX	PVC-PVC	8 x 1.5	11.2	238
0165003	Fe/CuNi	IEC-JX	PVC-PVC	8 x 1.5	11.2	238
0156003	NiCr/Ni	DIN-KCA	PVC-PVC	8 x 1.5	11.2	238
0166003	NiCr/Ni	IEC-KCA	PVC-PVC	8 x 1.5	11.2	238
0155005	Fe/CuNi	DIN-LX	PVC-PVC	12 x 1.5	13.3	335
0165005	Fe/CuNi	IEC-JX	PVC-PVC	12 x 1.5	13.3	335
0155007	Fe/CuNi	DIN-LX	PVC-PVC	16 x 1.5	15	447
0165007	Fe/CuNi	IEC-JX	PVC-PVC	16 x 1.5	15	447
0156007	NiCr/Ni	DIN-KCA	PVC-PVC	16 x 1.5	15	447
0166007	NiCr/Ni	IEC-KCA	PVC-PVC	16 x 1.5	15	447
0155010	Fe/CuNi	DIN-LX	PVC-PVC	24 x 1.5	19	555
0165010	Fe/CuNi	IEC-JX	PVC-PVC	24 x 1.5	19	555
0156010	NiCr/Ni	DIN-KCA	PVC-PVC	24 x 1.5	19	555
0166010	NiCr/Ni	IEC-KCA	PVC-PVC	24 x 1.5	19	555
Type SY with steel wire braiding						
0155501	Fe/CuNi	DIN-LX	PVC-PVC-S-PVC	4 x 1.5	11.4	240
0165501	Fe/CuNi	IEC-JX	PVC-PVC-S-PVC	4 x 1.5	11.4	240
0156501	NiCr/Ni	DIN-KCA	PVC-PVC-S-PVC	4 x 1.5	11.4	240
0166501	NiCr/Ni	IEC-KCA	PVC-PVC-S-PVC	4 x 1.5	11.4	240
0157501	PtRh/Pt	DIN-RCB/SCB	PVC-PVC-S-PVC	4 x 1.5	11.4	240
0167501	PtRh/Pt	IEC-RCB/SCB	PVC-PVC-S-PVC	4 x 1.5	11.4	240

Last Update (25.11.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16

Extension- and compensating cables, multi-paired

Article number	Thermocouple	Product Make-up	Cable design	Number of cores and mm ² per conductor	Outer diameter [mm]	Weight (kg/km)
0155502	Fe/CuNi	DIN-LX	PVC-PVC-S-PVC	6 x 1.5	13	355
0165502	Fe/CuNi	IEC-JX	PVC-PVC-S-PVC	6 x 1.5	13	355
0156502	NiCr/Ni	DIN-KCA	PVC-PVC-S-PVC	6 x 1.5	13	355
0166502	NiCr/Ni	IEC-KCA	PVC-PVC-S-PVC	6 x 1.5	13	355
0157502	PtRh/Pt	DIN-RCB/SCB	PVC-PVC-S-PVC	6 x 1.5	13	355
0167502	PtRh/Pt	IEC-RCB/SCB	PVC-PVC-S-PVC	6 x 1.5	13	355
0155503	Fe/CuNi	DIN-LX	PVC-PVC-S-PVC	8 x 1.5	13.8	410
0165503	Fe/CuNi	IEC-JX	PVC-PVC-S-PVC	8 x 1.5	13.8	410
0156503	NiCr/Ni	DIN-KCA	PVC-PVC-S-PVC	8 x 1.5	13.8	410
0166503	NiCr/Ni	IEC-KCA	PVC-PVC-S-PVC	8 x 1.5	13.8	410
0155505	Fe/CuNi	DIN-LX	PVC-PVC-S-PVC	12 x 1.5	17.9	550
0165505	Fe/CuNi	IEC-JX	PVC-PVC-S-PVC	12 x 1.5	17.9	550
0156505	NiCr/Ni	DIN-KCA	PVC-PVC-S-PVC	12 x 1.5	17.9	550
0166505	NiCr/Ni	IEC-KCA	PVC-PVC-S-PVC	12 x 1.5	17.9	550
0155507	Fe/CuNi	DIN-LX	PVC-PVC-S-PVC	16 x 1.5	19.4	730
0165507	Fe/CuNi	IEC-JX	PVC-PVC-S-PVC	16 x 1.5	19.4	730
0155510	Fe/CuNi	DIN-LX	PVC-PVC-S-PVC	24 x 1.5	23.8	847
0165510	Fe/CuNi	IEC-JX	PVC-PVC-S-PVC	24 x 1.5	23.8	847
Type ST with static overall screening						
0158500	Fe/CuNi	DIN-LX	PVC-ST-PVC	2 x 2 x 1.5	11.4	145
0168500	Fe/CuNi	IEC-JX	PVC-ST-PVC	2 x 2 x 1.5	11.4	145
0158501	NiCr/Ni	DIN-KCA	PVC-ST-PVC	2 x 2 x 1.5	11.4	145
0168501	NiCr/Ni	IEC-KCA	PVC-ST-PVC	2 x 2 x 1.5	11.4	145
0158503	Fe/CuNi	DIN-LX	PVC-ST-PVC	4 x 2 x 1.5	13.7	257
0168503	Fe/CuNi	IEC-JX	PVC-ST-PVC	4 x 2 x 1.5	13.7	257
0158504	NiCr/Ni	DIN-KCA	PVC-ST-PVC	4 x 2 x 1.5	13.7	257
0168504	NiCr/Ni	IEC-KCA	PVC-ST-PVC	4 x 2 x 1.5	13.7	257
0158506	Fe/CuNi	DIN-LX	PVC-ST-PVC	8 x 2 x 1.5	18.3	469
0168506	Fe/CuNi	IEC-JX	PVC-ST-PVC	8 x 2 x 1.5	18.3	469
0158507	NiCr/Ni	DIN-KCA	PVC-ST-PVC	8 x 2 x 1.5	18.3	469
0168507	NiCr/Ni	IEC-KCA	PVC-ST-PVC	8 x 2 x 1.5	18.3	469
0158509	Fe/CuNi	DIN-LX	PVC-ST-PVC	12 x 2 x 1.5	22.2	573
0168509	Fe/CuNi	IEC-JX	PVC-ST-PVC	12 x 2 x 1.5	22.2	573
0158510	NiCr/Ni	DIN-KCA	PVC-ST-PVC	12 x 2 x 1.5	22.2	573

Last Update (25.11.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16

Extension- and compensating cables, multi-paired

Article number	Thermocouple	Product Make-up	Cable design	Number of cores and mm ² per conductor	Outer diameter [mm]	Weight (kg/km)
0168510	NiCr/Ni	IEC-KCA	PVC-ST-PVC	12 x 2 x 1.5	22.2	573

Last Update (25.11.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16