

# **EPIC® H-B 10 TG**

Housing design H-B. The industry standard.

The robust low metal housing has a direct cable entry and pivots for a direct lever. It can be used for lighting and sound systems.

### Info

Non-slip ridges for comfortable disconnecting Protection rating UL50E tested







Supplementary automation components from Lapp



Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

## **Benefits**

The smallest housing with single and double lever. The right housing is available for every application

# **Application range**

Plant engineering Light & sound technology Plastics industry

### **Product features**

Hood, low version

Last Update (01.06.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02\_03.16



# EPIC® H-B 10 TG

Bolts for double lever Straight cable entry Versions with / without neck

**Technical Data** 

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range: -40°C to +100°C, short-term up to +125°C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



# EPIC® H-B 10 TG

### М PG Pieces / PU Article number Article description Neck H-B housing: hood (straight cable entry, bolts for double lever) H-B 10 TG 16 10 10040000 16 yes H-B 10 TG 21 21 10 10040100 yes 20 19040000 H-B 10 TG M20 10 25 H-B 10 TG M25 10 19040100