

# **EPIC® H-B 10 TG-RO**

Housing design H-B. The industry standard.

The robust universal low housing is available with or without a neck and can be used, for example, in the plastics industry.

### Info

Non-slip ridges for comfortable disconnecting Protection rating UL50E tested







Supplementary automation components from Lapp



Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

### **Benefits**

The smallest housing with single and double lever. The right housing is available for every application

## **Application range**

Plant engineering Light & sound technology Plastics industry

### **Product features**

Hood, low version

Last Update (01.06.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02\_03.16



# **EPIC® H-B 10 TG-RO**

Reels for single lever Versions with / without neck

**Technical Data** 

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

JL-tested:

UL File Number: E75770

Temperature range: -40°C to +100°C, short-term up to +125°C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



# EPIC® H-B 10 TG-RO

### М PG Pieces / PU Article number Article description Neck H-B housing: hood (straight cable entry, bolts for single lever) 10 10040900 H-B 10 TG-RO 16 16 yes H-B 10 TG-RO 21 21 10 10040700 yes 19040900 H-B 10 TG-RO M20 20 10 25 H-B 10 TG-RO M25 10 19040700