

ÖLFLEX® SOLAR XLWP

Electron beam cross-linked solar cables with optimized performance in water - EN 50618 type

ÖLFLEX® SOLAR XLWP, electron beam cross-linked solar cable with optimized performance in water

Info

Optimised cable design - high volume resistance even after long-term period in water

H1Z2Z2-K type certified according to EN 50618

Burial-related UL 854 Impact- and Crushing-Resistance



Solar Energy



Suitable for outdoor use



Halogen-free



Cold-resistant



Acid-resistant



Temperature-resistant



UV-resistant



Waterproof

Last Update (03.02.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® SOLAR XLWP



Benefits

The alternative for water coverage, e.g. due to elevated water line caused by flooding
Reduction of flame propagation and of toxic combustion gases in the event of fire
Robust against mechanical impacts
Extruded colour stripe serves as reverse polarity protection during installation.
Exact quantity control during installation by meter marking on the cable sheath

Application range

Photovoltaic systems with DC system voltage up to 1800 V to ground
For the cabling between the solar modules and as extension cable between the module strings and the DC/AC inverter
Flexible or building-integrated PV systems
Underground use without protection conduit/ duct in professionally built cable trench with at least 50 cm of back-fill soil (70 cm underneath roads), above indicating tape, above covering plastic slab, above at least 10 cm of covering sand layer, above the cable laid on at least 10 cm high sand bed layer (cf.: VDE 0891-6, Section 4.2)
In September 2018 and based on AD8 watertightness, this product was recommended by Solartechnik Bayern for underground use typically realized via underground conduits/ ducts (...) for PV applications

Product features

Weather/ UV resistant per EN 50618, Annex E, as well as ozone resistant per EN 50396;
Transversely watertight "AD8" per IEC 60364-5-51/ HD 60364-5-51, IEC 62440, and EN 50525-2-21 down to 1 metre in water depth
Halogen-free and flame-retardant
Good notch and abrasion resistance
Tested against burial-related, mechanical UL 854 Tests Impact-Resistance and Crushing-Resistance
XLWP = X-Linked + Water-Proof (Permanent water contact AD8 acc. to IEC 60364-5-51, 1 mtr. in max. submersion depth @ temperature of widely unmoved water between 5 °C and 40 °C),
Proven electron beam cross-linked quality

Norm references / Approvals

H1Z2Z2-K type certified according to EN 50618
Items with other cross-sections on request

Product Make-up

Fine-wire, tinned-copper conductor
Core insulation made of electron beam cross-linked copolymer
Colour of core insulation: white
Outer sheath made of electron beam cross-linked copolymer
Outer sheath colour: Black only, or Black with Red or Blue stripe

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001578 ETIM 6.0 Class-Description: Flexible cable
Conductor stranding:	Fine wire according to VDE 0295,

Last Update (03.02.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® SOLAR XLWP

	class 5/IEC 60228 class 5
Minimum bending radius:	D \leq 8mm: 4D; 8<D \leq 12mm: 5D; D>12mm: 6D *D = Cable's outer diameter
Nominal voltage:	AC U ₀ /U: 1.0/1.0 kV DC U ₀ /U: 1.5/1.5 kV Max. permissible DC operating voltage: 1.8 kV
Test voltage:	AC 6500 V
Current rating:	I _m compliance with EN 50618, Table A.3
Temperature range:	-40°C to +120°C max. conductor temperature based on EN 60216-1 Ambient temperature range according to EN 50618: -40°C to +90°C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: Coil 100 m; Drum (500; 1000) m

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

ÖLFLEX® SOLAR XLWP

Article number	Conductor cross-section (mm ²)	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
1023601	4	5.8	38.4	68.1
1023602	6	6.4	57.6	91.6
1023603	10	7.6	96	138.6
1023604	16	9.1	153.6	209.7
Core insulation: white / Outer sheath: black with red stripe				
1023621	4	5.8	38.4	68.1
1023622	6	6.4	57.6	91.6
1023623	10	7.6	96	138.6
1023624	16	9.1	153.6	209.7

Last Update (03.02.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16