

ÖLFLEX® TRAY II CY

ÖLFLEX® Control Cable 0.6/1 kV, UL TC-ER 600V AWM WET OIL/ SUN RES TRAY Screened

ÖLFLEX® TRAY II CY: UL TC-ER 600V, AWM 1000V WET 75 °C SUN/ OIL RES I+II DIR BUR CSA AWM I/II A/B FT4 Screened PVC power control cable 0.6/1 kV, Tray Exposed Run

Info

Outdoor use in USA

Broad application range (NFPA 70/NEC), NFPA 79 compliance

EMC/Screened



Suitable for outdoor use



Flame-retardant



Cold-resistant



Mechanical resistance



Oil-resistant



Interference signals



Torsion-resistant



UV-resistant

Last Update (09.11.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® TRAY II CY

Benefits

Many certifications/ use types
 Cost-saving, fast installation omitting protection systems
 75 °C WET Rating + Sunlight Resistant Rating: Outdoor use in the USA
 Electromagnetic field screening

Application range

Industrial machinery, plant engineering in the USA
 Unprotected 600V operation on cable tray in the USA, incl. 6 ft. Exposed Run laying sections for version with at least 3 conductors
 Compliant with Tool machines: (UL) MTW
 Outdoor use and Direct Burial in the USA, per UL 1277
 USA Wind Turbine Tray Cable (WTTC) do turbin wiatrowych

Product features

Flame-retardant according to CSA FT4
 UL Vertical-Tray Flame Test
 Oil-resistant according to UL OIL RES I & II
 Water-resistant, UL 75 °C WET rating
 UV resistant (SUN RES), Ozone resistant
 Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

Norm references / Approvals

USA: (UL) TC-ER [E171371], (UL) MTW [E155920], (UL) WTTC [E323700], Submersible Pump (14 - 2 AWG), (UL) PLTC-ER (18 - 12 AWG) [E216027], (UL) ITC-ER (18 - 12 AWG) [E196134], (UL) DP-1 [E233406], UL AWM (18 - 2 AWG) [E100338]
 UL OIL RES I/ II, 75 °C WET, 90 °C DRY, SUN RES, DIR BUR, NEC/NFPA 70, NFPA 79
 CAN: c(UL) CIC/ TC 600V FT4 (< 250 kcmil) [E171371], CSA AWM I/II A/B FT1

Product Make-up

Fine-wire strand made of bare copper wires
 Insulation: PVC+nylon sheath (PA skin)
 Aluminum-coated foil
 Tinned-copper braiding
 Outer jacket: Specially formulated thermoplastic polymer
 Color of the outer jacket: Black

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000104 ETIM 6.0 Class-Description: Control cable
Core identification code:	Black with white numbers
Conductor stranding:	Fine copper wire strands
Torsion movement in WTG:	TW-0 & TW-2, refer to Appendix T0
Minimum bending radius:	6 x OD
Nominal voltage:	UL/CSA: 600 V (TC, MTW, CIC), WTTC 1000 V UL/CSA: 1000 V (AWM) IEC: $U_0/U = 600/1000$ V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor

Last Update (09.11.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® TRAY II CY

Temperature range: -40°C (static)/ -25°C (occ. moved) to +90°C (TC) or +105°C (AWM)

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 610 m drum or 8 x 76 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

ÖLFLEX® TRAY II CY

Article number	Number of cores and mm ² per conductor	AWG per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® Tray II CY					
2218030	3 G 1.0	-	8.2	35.1	119
2218040	4 G 1.0	-	8.8	55.2	137
2218050	5 G 1.0	-	9.4	65.8	149
2218070	7 G 1.0	-	10.1	86.9	193
2218120	12 G 1.0	-	12.9	149.3	330
2218180	18 G 1.0	-	15.7	214.2	438
2218250	25 G 1.0	-	17.7	354.2	574
2216030	3 G 1.5	-	8.9	59.8	144
2216040	4 G 1.5	-	9.6	74.5	173
2216050	5 G 1.5	-	10.3	93.5	189
2216070	7 G 1.5	-	11.3	130.5	246
2216120	12 G 1.5	-	15.1	213.8	426
2216180	18 G 1.5	-	17.3	312.4	515
2216250	25 G 1.5	-	19.6	415.6	708
2214030	3 G 2.5	-	9.8	91.2	180
2214040	4 G 2.5	-	10.7	125.7	223
2214050	5 G 2.5	-	11.6	150.1	268
2214070	7 G 2.5	-	12.5	201.2	327
2214120	12 G 2.5	-	16.9	333.6	595
2214180	18 G 2.5	-	19.5	487.6	784
2214250	25 G 2.5	-	23.3	685.1	1048
2212040	4 G 4.0	-	12.5	186.4	315
2212070	7 G 4.0	-	15.5	310.2	499
2210040	4 G 6.0	-	15.5	271.7	552
2208040	4 G 10.0	-	18.7	438.6	857
2206040	4 G 16.0	-	23.3	699	1208
2204040	4 G	4	28.6	1,296.8	1982
2202040	4 G	2	33.2	1,899.5	2903

Last Update (09.11.2021)

©2021 Lapp Group - Technical changes reserved

 Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16