

Circular connectors for servomotors and power supply

EPIC® M12 Power cable connector, 630V and 12A, screw connection 0.75-1.5mm²

Info

smallest Power connector Made in Germany







Low weight



Space requirement



Waterproof

Benefits

to terminate only screw driver is neccessary Small and space-saving for narrow available space high performance gold plated contacts

Application range

Power Supply for small devices for 1-phase cables or 3-phase wihout N

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC002635

ETIM 5.0 Class-Description: Circular connector (industrial

connector)

Classification ETIM 6: ETIM 6.0 Class-ID: EC002635

ETIM 6.0 Class-Description: Circular connector (industrial

connector)

Rated voltage (V): 630 V

Last Update (03.02.2021) ©2021 Lapp Group - Technical changes reserved Product Management www.lappkabel.de You can find the current technical data in the corresponding data sheet. PN 0456 / 02_03.16



Rated impulse voltage: 6 kV
Rated current (A): 12 A
Pollution degree: 3

Contact resistance: < 3 mOhm

Number of contacts: 3 + PE

S-coded

Termination methods: Screw termination: 0.75 - 1.5mm²

Protection rating: IP 67

Cycle of mechanical operation: 100

Temperature range: -40 °C to +85 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



Clamping range max Article number Article description Clamping range min Pieces / PU 44423140 Cable coupler with pin contacts 10 8 44423141 Cable connector with socket 10 contacts 44423142 Cable coupler with pin contacts, 8 10 angled 8 10 44423143 Cable connector with socket contacts, angled



