

EPIC® SOLAR 4 Splitter

Connector system for weatherproof cabling of photovoltaic systems

Info

4 mm connector system with double hook
Splitter for parallel connection of photovoltaic modules



Solar Energy



Suitable for outdoor use



Voltage



Temperature-resistant



UV-resistant



Waterproof

Benefits

Splitter for parallel connection of PV-modules and strings
Easy plug and play
Fixing option for a clear installation with a Ø 5mm mounting hole

Application range

Photovoltaic plants
Crystalline and thin-film constructions
Solartracker

Product features

Mateable with EPIC® SOLAR 4 THIN, EPIC® SOLAR 4PLUS, EPIC® SOLAR 4

Last Update (28.10.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

EPIC® SOLAR 4 Splitter

Splitter MFF 1x connection male, 2x connection female
Splitter MFF 1x connection female, 2x connection male

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC002635 ETIM 5.0 Class-Description: Circular connector (industrial connector)
Classification ETIM 6:	ETIM 6.0 Class-ID: EC002635 ETIM 6.0 Class-Description: Circular connector (industrial connector)
Rated voltage (V):	1000 V AC/DC
Rated impulse voltage:	8 kV
Rated current (A):	30 A
Pollution degree:	3
Protection rating:	IP65/IP67
Cycle of mechanical operation:	100
Protection class:	II
Temperature range:	-40 °C ... +85 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

EPIC® SOLAR 4 Splitter

Article number	Article designation	PU
EPIC® SOLAR 4 Splitter		
44428226	EPIC® SOLAR 4 Splitter MFF	25
44428227	EPIC® SOLAR 4 Splitter FMM	25

Last Update (28.10.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

EPIC® SOLAR 4 Splitter

