

## SKINDICHT® RWV

SKINDICHT® RWV, corrosion- & seawater-resistant angle cable gland with incised sealing ring as sealing, to decrease in installation height



Corrosion-resistant



Space requirement



Robust

### Benefits

- Strain relief
- Sealed by incised sealing ring
- Corrosion-resistant
- Decrease in installation height
- Seawater-resistant

### Application range

- Angled glands are used in areas where cables have to run in parallel to the housing wall.
- Electric motor manufacturing
- Machine and equipment manufacturing
- Plant engineering
- Light and sound applications

### Product Make-up

PG connection thread

### Note

Counter nut to be used: SKINDICHT® SM  
 For combination with other SKINDICHT® or SKINTOP® cable glands, we propose our SKINDICHT® RWV without incised sealing ring (E) and compression screw (D)

Last Update (10.01.2022)

©2022 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## SKINDICHT® RWV

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable screw gland
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000441 ETIM 6.0 Class-Description: Cable screw gland
Material:	Body: zinc die-casting Compression screw and hexagon nut: nickel-plated brass Incised sealing ring: CR O-ring: NBR
Protection rating:	IP 55
Temperature range:	-20°C to +80°C Without incised sealing ring: -20°C to +100°C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.  
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SKINDICHT® RWV**

Article number	Article designation / size	A (mm)	G mm	Ø B mm	Incised sealing ring ØF (mm)	Overall length C mm	Thread length D mm	SW1/SW2 mm	Pieces / PU
<b>SKINDICHT® RWV</b>									
52004180	PG 7	20.5	14	15.3	5	26.0	8.5	15.0 / 13.0	25
52004190	PG 9	23.5	17	18.3	5/8	28.0	9.5	18.0 / 15.0	25
52004200	PG 11	26	20	21.9	7/10/12.5	31.5	10	21.0 / 18.0	25
52004210	PG 13,5	28.5	22	24	7/10.5/13/16	34.5	10.5	23.0 / 20.0	25
52004220	PG 16	31	24	26.1	8/10.5/13.5/16	35.5	11	26.0 / 22.0	10
52005420	PG 21	33.5	30	32.5	11/15/18/20	42.5	11.5	32.0 / 28.0	10
52004225	PG 29	43	40	42	19/23/27/31	49.0	13	41.0 / 37.0	10
<b>SKINDICHT® RWV without E+D</b>									
52024020	PG 7	20.5	14	15.3	-	20.2	8.5	15.0 / 13.0	25
52023970	PG 9	23.5	17	18.3	-	21.8	9.5	18.0 / 15.0	25
52023980	PG 11	26	20	21.9	-	24.9	10	21.0 / 18.0	25
52023990	PG 13,5	28.5	22	24	-	27.4	10.5	23.0 / 20.0	25
52024000	PG 16	31	24	26.1	-	28.5	11	26.0 / 22.0	10
52024010	PG 21	33.5	30	32.5	-	34.8	11.5	32.0 / 28.0	10
52024015	PG 29	43	40	42	-	41.2	13	41.0 / 37.0	10

Last Update (10.01.2022)

©2022 Lapp Group - Technical changes reserved

 Product Management [www.lappkabel.de](http://www.lappkabel.de)

 You can find the current technical data in the corresponding data sheet.  
 PN 0456 / 02\_03\_16

## SKINDICHT® RWV

