

SILVYN® HIPROSILTAPE

SILVYN® HIPROSILTAPE - silicone tape for SILVYN® HIPROJACKET

Info

Outstanding protection for extreme impact of heat



Benefits

Heat-resistant

Flexible

The protection rating increases to IP67 if SILVYN® HIPROSILTAPE is also used

Temporarily reduces the temperature in the conduit by up to 30 %

Application range

Heavy industry, iron and steel works, foundries, glass and ceramic processing, chemical industries

Steel industry

Railway applications / vehicle construction

Mechanical engineering

Used in areas where cables and wires are exposed to extreme heat

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000128

ETIM 5.0 Class-Description: Adhesive tape

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000128

ETIM 6.0 Class-Description: Adhesive tape

Colour delivered:

Red

Material:

Silicone-rubber compound, self-vulcanising, halogen-free

Temperature range:

-55 °C to +260 °C permanent temp.

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

SILVYN® HIPROSILTAPE

Article number	Nominal size	ID x OD mm	PU ring (m)
SILVYN® HIPROSILTAPE			
61713040	25	25.0 x 0.5	11

Last Update (1.01.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16