

SILVYN® SI

SILVYN® SI - grey soft PVC conduit



Flame-retardant



Low weight

Benefits

Protection against dust
Protection against humidity
Low abrasion protection

Application range

Easy cable protection
Additional insulation
Bundling and guiding of cables and wires

Product features

Flexible
Soft

Product Make-up

Soft-PVC conduit

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC001177

ETIM 5.0 Class-Description: Protective plastic hose

Classification ETIM 6:

ETIM 6.0 Class-ID: EC001177

ETIM 6.0 Class-Description: Protective plastic hose

Note:

Flame-retardant and self-extinguishing

Last Update (20.10.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SILVYN® SI

	Dielectric strength: 25 kV/mm
	Tear-resistance: 23 N/mm ²
	Shore A hardness: 75 °C to 90 °C
Colour delivered:	Silver grey (RAL 7001)
Material:	Soft PVC
Temperature range:	-5 °C to +80 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

SILVYN® SI

Article number	ID x OD mm	Suitable for SILVYN® SSV-M/SSVZ-M	Suitable for SILVYN® SSV/SSVZ	Suitable for SILVYN® SCH	PU ring (m)
SILVYN® SI					
61713210	7.0 x 9.0	12/1 / -	-	10 - 16 S	50
61713240	9.0 x 12.0	12/2 / -	-	10 - 16 S	50
61713270	11.0 x 14.0	16/1 / -	-	10 - 16 S	50
61713300	13.0 x 16.0	16/2 / -	-	12 - 20 S	50
61713330	14.0 x 18.0	20/1	-	12 - 20 S	50
61713360	18.0 x 22.0	20/3	13,5/1	16 - 25 S	50
61713390	23.0 x 28.0	25	21	20 - 32 S	50
61713420	32.0 x 38.0	32 / 32/2	29/2	32 - 50 S	50

Last Update (20.10.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16