

## SILVYN® SI

SILVYN® SI - grey soft PVC conduit



Flame-retardant



Low weight

### Benefits

Protection against dust  
Protection against humidity  
Low abrasion protection

### Application range

Easy cable protection  
Additional insulation  
Bundling and guiding of cables and wires

### Product features

Flexible  
Soft

### Product Make-up

Soft-PVC conduit

### Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC001177

ETIM 5.0 Class-Description: Protective plastic hose

Classification ETIM 6:

ETIM 6.0 Class-ID: EC001177

ETIM 6.0 Class-Description: Protective plastic hose

Note:

Flame-retardant and self-extinguishing

Last Update (07.10.2021)

©2021 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

**SILVYN® SI**

|                    |                                       |
|--------------------|---------------------------------------|
|                    | Dielectric strength: 25 kV/mm         |
|                    | Tear-resistance: 23 N/mm <sup>2</sup> |
|                    | Shore A hardness: 75 °C to 90 °C      |
| Colour delivered:  | Silver grey (RAL 7001)                |
| Material:          | Soft PVC                              |
| Temperature range: | -5 °C to +80 °C                       |

**Note**

Photographs and graphics are not to scale and do not represent detailed images of the respective products.  
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SILVYN® SI**

| Article number | ID x OD mm  | Suitable for SILVYN® SSV-M/SSVZ-M | Suitable for SILVYN® SSV/SSVZ | Suitable for SILVYN® SCH | PU ring (m) |
|----------------|-------------|-----------------------------------|-------------------------------|--------------------------|-------------|
| SILVYN® SI     |             |                                   |                               |                          |             |
| 61713210       | 7.0 x 9.0   | 12/1 / -                          | -                             | 10 - 16 S                | 50          |
| 61713240       | 9.0 x 12.0  | 12/2 / -                          | -                             | 10 - 16 S                | 50          |
| 61713270       | 11.0 x 14.0 | 16/1 / -                          | -                             | 10 - 16 S                | 50          |
| 61713300       | 13.0 x 16.0 | 16/2 / -                          | -                             | 12 - 20 S                | 50          |
| 61713330       | 14.0 x 18.0 | 20/1                              | -                             | 12 - 20 S                | 50          |
| 61713360       | 18.0 x 22.0 | 20/3                              | 13,5/1                        | 16 - 25 S                | 50          |
| 61713390       | 23.0 x 28.0 | 25                                | 21                            | 20 - 32 S                | 50          |
| 61713420       | 32.0 x 38.0 | 32 / 32/2                         | 29/2                          | 32 - 50 S                | 50          |

Last Update (07.10.2021)

©2021 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)You can find the current technical data in the corresponding data sheet.  
PN 0456 / 02\_03\_16