

Shrink tube PROTECT-C

The PROTECT-C shrink tube with adhesive coating inside offers a good chemical resistance and high weather-resistance. The shrink ratio is 3:1.

Info

Double walled





Good chemical resistance



Mechanical resistance



Waterproof

Benefits

Good chemical resistance High mechanical stability Good weather-resistance High shrink ratio and adhesive coating

Application range

Particularly suitable for corrosion and damp protected casings as well as highly contoured components

Product features

Adhesive lining bonds to plastic, rubber, neoprene, steel and polyethylene Silicone-free UV-resistant

Included

Plastic bag with 0.6 m units

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC000217

ETIM 5.0 Class-Description: Heat-shrink tubing

Classification ETIM 6: ETIM 6.0 Class-ID: EC000217

Last Update (11.01.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16





Shrink tube PROTECT-C

ETIM 6.0 Class-Description: Shrink tubing

Note: Double-walled

Dielectric strength: 15 kV/mm

Info: Shrinking ratio: 3:1

Colour delivered: Black

Material: Cross-linked modified polyolefin, with thermoplastic adhesive

coating inside

Silicone, Cadmium and Lead free

Temperature range: -55 °C to +110 °C

Shrinking temperature: > 100°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



Shrink tube PROTECT-C

| Article number | Article description | J 0 () | Panel thickness, shrunk +- 0.1 mm | PU (m) | PU |
|----------------|---------------------|---------|--------------------------------------|--------|----|
| 61742449 | PROTECT-C 3/1 BK | 3 - 1 | 1.0 | 12 | 1 |
| 61742450 | PROTECT-C 6/2 BK | 6 - 2 | 1.1 | 9 | 1 |
| 61742451 | PROTECT-C 9/3 BK | 9 - 3 | 1.3 | 6 | 1 |
| 61742452 | PROTECT-C 12/4 BK | 12 - 4 | 1.7 | 5.4 | 1 |
| 61742453 | PROTECT-C 18/6 BK | 18 - 6 | 2.0 | 3.6 | 1 |
| 61742454 | PROTECT-C 24/8 BK | 24 - 8 | 2.5 | 3 | 1 |