

SILVYN® LCC-2

SILVYN® LCC-2 is a metal conduit with one-hook profile, offers good flexibility and a liquidtight PVC jacket



Mechanical resistance



Robust



UV-resistant



Waterproof

Benefits

Protects against liquids
High-tensile
High crush-resistance
Suitable for outdoor use and direct burial
High mechanical resistance

Application range

Mechanical engineering
Plant engineering
Outdoors
Used in areas where liquids are present
Applications with high mechanical stress

Product Make-up

Helically-wound metal protective conduit with interlocked profile
PVC sheath

Note

Last Update (10.01.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SILVYN® LCC-2

Upon request: Grey colour

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001179 ETIM 5.0 Class-Description: Protective metallic hose
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001179 ETIM 6.0 Class-Description: Protective metallic hose
Norm references / Approvals:	IEC EN 61386-23
Colour delivered:	Black (RAL 9005), UV-resistant
Material:	Inner conduit: steel, galvanised Outer sheath: PVC
Temperature range:	-15°C to +70°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

SILVYN® LCC-2

Article number	Nominal size	ID x OD mm	Bending radius (mm)	Suitable for SILVYN® LGF-2-M/LGS-2-M	PU ring (m)
SILVYN® LCC-2					
61804702	10	6.8 x 10.0	25	M12x1,5	30
61804712	12	10.2 x 14	40	M16x1,5/1	30
61804722	16	13 x 17	45	M16x1,5/2 + M20x1,5/1	30
61804732	20	16.9 x 21.5	50	M20x1,5/2	30
61804742	25	21.1 x 26	60	M25x1,5	30
61804752	32	28.1 x 34	90	M32x1,5	30
61804762	40	37.6 x 44.5	120	M40x1,5	10
61804772	50	48.4 x 55	130	M50x1,5	10
61804792	63	57.5 x 64.5	160	M63x1,5	10
61804787	75	70 x 79	190	M75x1,5	10

Last Update (10.01.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16