

EPIC® H-B 16 TSH

Housing design H-B. The industry standard.

The robust metal housing is suitable for use in the plastics industry and is available with or without a neck.

Info

Non-slip ridges for comfortable disconnecting More interior space for wiring Protection rating UL50E tested







Supplementary automation components from Lapp



Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

Benefits

The housing standard. Wide choice for all applications M40 housing extension on M50 with SKINTOP 53112083 possible (clamping range 27 - 35 mm)

Application range

Plant engineering Light & sound technology Plastics industry

Last Update (07.10.2021)
©2021 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16



EPIC® H-B 16 TSH

Product features

Hood, high version Bolts for double lever Side cable entry Versions with / without neck

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range: -40°C to +100°C, short-term up to +125°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® H-B 16 TSH

| Article number | Article description | М | PG | Neck | Pieces / PU |
|--|---------------------|----|----|------|-------------|
| H-B housing: hood (side cable entry, bolts for double lever, high version) | | | | | |
| 70102200 | H-B 16 TSH 21 | - | 21 | yes | 5 |
| 70102400 | H-B 16 TSH 29 | - | 29 | yes | 5 |
| 79102200 | H-B 16 TSH M25 | 25 | - | - | 5 |
| 79102400 | H-B 16 TSH M32 | 32 | - | - | 5 |
| 79102800 | H-B 16 TSH M40 | 40 | - | - | 5 |