

CAT. N° 0 019 66



## KEY LOCK - N° 850 - FOR 2 AND 3 ROWS DISTRIBUTION PLEKO<sup>3</sup> CABINETS

|                           |       |
|---------------------------|-------|
| Pack (number of units)    | 1     |
| Volume (dm <sup>3</sup> ) | 0,211 |
| Weight (g)                | 47,00 |

### Product characteristics

#### Accessories

##### Key lock

- Key lock N° 850

### General characteristics

#### Plexo<sup>3</sup> - IP 65 weatherproof cabinets, multifunction sleeves and accessories

- Self-extinguishing: resistance to incandescent wire 650°C.
- Allows to achieve assemblies conform to IEC 61 439 - 3
- Weatherproof cabinets - IP 65 - IK 09 - Class II
- Door and cabinet fully reversible. Removable chassis and faceplates from 2-row versions up
- 2-position rail for modular products and moulded cases. Spacing between rails 150 mm
- Can be fitted with perforated plates and solid faceplates for mounting non-modular products
- Lockable door handle, sealable cover and faceplate
- Shock-resistant polystyrene material
- Box colour light grey L750A, cover colour dark grey R746A
- Supplied without terminal blocks

### Documentation



#### Catalogue pages & additional information

- [Description page \(p.220\)](#)
- [Technical page \(p.221\)](#)
- [Description page \(p.286\)](#)
- [Technical page \(p.287\)](#)



#### Agreements & certificates of conformity

- [OC / CB-654748](#)



#### Installation instructions & related documents

- [LE02494AD\\_01](#)