

CAT. N° 0 205 58



SUPPORT FRAME XL³ 4000 - FIXED - H. 2000 - FOR ENCLOS. W.725/975 WITHOUT SLEEVES

Pack (number of units)	1
Volume (dm ³)	11
Weight (g)	4 200,00

Product characteristics

Equipment

Support frame for faceplates

- Fixed for enclosure width 725 mm or enclosure width 975 mm without internal cable sleeves
- Height : 2000 mm

General characteristics

Distribution enclosures XL³ 4000

- IP 30 - IK 07
- IP 55 - IK 08 with door and sealing kit for use when joining enclosures
- Consist of the combination of a "roof-base" assembly, structural uprights, functional uprights, rear and side panels RAL 7035, plinths RAL 7004
- Height 2000 or 2200 mm.
- Capacity 24 modules (enclosures width 725 or width 975 with internal cable sleeve), 36 modules (enclosures width 975)
- Usable faceplate height 1800 mm (1700 mm only if using the pivoting support frame) or 2000 mm

Documentation



Catalogue pages & additional information

- [Description page \(p.266\)](#)
- [Technical page \(p.267\)](#)
- [Selection chart \(p.268\)](#)
- [XL3 4000 equipment for mounting on adjustable plates](#)



Agreements & certificates of conformity

- [LOVAG-IT 12](#)
- [LOVAG-IT 12](#)
- [LOVAG-IT 12](#)