

CAT. N° 0 262 50



## CAGE TERMINALS (4) - FOR DPX 630 - FOR RIGID CABLE 300 MM<sup>2</sup> / 240 MM<sup>2</sup> FLEXIBLE

Pack (number of units)	1
Volume (dm <sup>3</sup> )	1,006
Weight (g)	479,00

### Product characteristics

#### Accessories

##### Cage terminals

- Set of 4 terminals for cable 300 mm<sup>2</sup> max. (rigid) or 240 mm<sup>2</sup> max. (flexible)

### General characteristics

#### DPX™-IS 630 isolating switches - 400 to 630 A

- Isolating switches for on-load circuit breaking by visible isolation and positive action of the contacts
- Padlock integrated in the handle
- Supplied with terminal shields, and cage terminals
- Conform to IEC 60947-3
- Category of use AC 23 A
- Accept electrical auxiliaries
- Can be mounted on plate in XL<sup>3</sup> enclosures

### Documentation

#### Catalogue pages & additional information

- [Description page \(p.131\)](#)
- [Technical page \(p.132\)](#)
- [Technical page \(p.133\)](#)
- [Description page \(p.149\)](#)
- [Description page \(p.168\)](#)
- [Technical page \(p.170\)](#)
- [DRXTM 630 adjustable](#)
- [DPX<sup>3</sup> 160/250/630 & 1600](#)
- [DPX<sup>3</sup> 630](#)
- [DPXTM-IS 630 isolating switches](#)

#### Installation instructions & related documents

- [LE04940AB](#)