

CAT. N° 0 362 16



CABLE DUCTING LINA 25 - WIDTH 80 X HEIGHT 60 MM - BLUE 2525 - L. 2 M

Pack (number of units)	24
Volume (dm³)	86
Weight (g)	20 600,00

Product characteristics

Lina 25 ducting

- PVC Blue 2525 according to AFNOR NF X08-002
- Conform to EN 50085-2-3
- 6.5 mm wide fingers with a 6 mm spacing
- Accepts up to 6 mm² without breaking side wall fingers
- Two pre-scored lines allow removal of fingers
- Bump on side wall fingers help cabling
- Rounded fingers prevent injury during cabling
- Conform to EN 50085 parts 2 and 3
- Plastic cable ducting (base + cover)
- Side perforations at intervals of 12.5 mm. Length: 2 m
- Width x height : 80 x 60 mm

General characteristics

Lina 25™ ducting and halogen-free trunking

Documentation

🔢 Catalogue pages & additional information

- Description page (p.348)
- Technical page (p.349)

G Agreements & certificates of conformity

- NF 004-641237C
- <u>UL recogn-E212478</u>
- CSA-700861

Installation & technical data

F01892EN-00

^{*} All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis: before-tax price list, May 2018