

CAT. N° 0 371 52



TERMINAL BLOCK VIKING 3 -SCREW -METAL BASE -3 CONNECT ON 3 LEVELS -PITCH 5 -GREY

Pack (number of units)	50
Volume (dm ³)	2,061
Weight (g)	1 154,00

Product characteristics

For sensors and actuators

- For connecting sensors (Cat.No 0 371 51) or actuators (Cat.No 0 371 52), and their shared power supply unit using equipotential bridging comb Cat.Nos 0 375 46/47

3 connections on 3 levels - for actuator

- Green/yellow marking for the lower level
- Metal base
- Screwless fixing on rail
- Rigid wire capacity: 2.5 mm² max. with equipotential bridging comb
- Colour : Grey
- Nominal cross-section : 2.5 mm²
- Capacity – Rigid wire : 0.25 to 4 mm²
- Capacity – Flexible wire with or without ferrules : 0.25 to 2.5 mm²
- Pitch : 5 mm

General characteristics

Viking™ 3 terminal blocks with screw connection - for copper cables

- Used to make the electrical connection between 2 flexible copper wires with or without ferrules or 2 rigid copper wires
- 2 areas for automatic insertion bridging combs up to 8 pitch (upper level only for multi-level blocks)
- For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm

Documentation

Catalogue pages & additional information

- [Selection chart \(p.324-325\)](#)
- [Description page \(p.328\)](#)
- [Description page \(p.329\)](#)
- [Technical page \(p.335\)](#)
- [Viking™ 3 terminal blocks with screw connection](#)

Agreements & certificates of conformity

- [Ex-002/G](#)
- [IMQ-CA02](#)
- [VERITAS \(BV\)-23393/C0 BV](#)
- [NF App Industri-NF208_1008](#)
- [UL recogn-20101029-E60900](#)
- [ATEX-LCIE 16 ATEX 3049U - 02](#)

Installation & technical data

- [F00671EN-02](#)