

CAT. N° 0 390 14



## POWER TERMINAL BLOCK VIKING 3 - CABLE LUG-CABLE LUG - PITCH 42

Pack (number of units)	5
Volume (dm <sup>3</sup> )	7,84
Weight (g)	1 986,00

### Product characteristics

#### Insulated aluminium/copper power terminal blocks

- For aluminium/copper cables, copper bars or cable lugs
- Direct connection of cable
- Insulation and protection against direct contact without additional accessories (built-in dividers and covers)
- Pre-cut removable covers for adjustment to the various connection modes
- Fixed using metal clip for rails 15 mm depth and EN 60715 15 mm depth, or on plate with screws
- Permits the use of Cab 3, Duplix markers
- Test via test plug closed covers
- Blocks with identical pitch can be joined using a threaded rod
- Shunting possible with Cat.Nos 0 394 46/47

#### Cable lug - cable lug

- Rigid or flexible cable : Al/Cu 150 mm<sup>2</sup>
- Rigid or flexible cable : Al/Cu 150 mm<sup>2</sup>
- Pitch : 42 mm

### General characteristics

#### Viking™ 3 power terminal blocks

- Bridging the gap between the enclosure and external cables

### Documentation



#### Catalogue pages & additional information

- [Description page \(p.338\)](#)
- [Technical page \(p.339\)](#)



#### Agreements & certificates of conformity

- [UL recogn-E60900 Vol 1 Sec7](#)