

CAT. N° 0 489 18



BUS/KNX PRESENCE SENSOR - CEILING MOUNTED - IP20 - 360° IR AND ULTRASOUND - 8 M

Pack (number of units)	1
Volume (dm ³)	1,563
Weight (g)	180,00

Product characteristics

Special presence sensors for work areas

- Suitable for meeting rooms, classrooms, open areas, etc.

Ceiling mounted

- 360° passive infrared and ultrasound detection, range 8 m
- IP 20
- Consumption 0.5 W
- Optimum distance between two sensors: 6 m
- Fixes directly in suspended ceiling with springs (supplied) or is installed in a 50 mm deep Batibox
- Surface mounted on ceiling using accessory Cat.No 0 488 75
- Connection by KNX red/black connector

General characteristics

Lighting Management - BUS/KNX sensors

- Constantly check for presence and light levels, switching OFF as soon as the natural light level is sufficient Switch ON and OFF automatically
- Accurate set-up on site with configuration device
- Connected directly to BUS/KNX cable (supplied with tap-off connector)
- The detector must be programmed using ETS software

Documentation

Catalogue pages & additional information

- [Description page \(p.673\)](#)
- [Selection chart \(p.674\)](#)

Installation & technical data

- [S000085219EN-1](#)
- [LE05504AB_EN](#)

Installation instructions & related documents

- [LE07225AC](#)

Agreements & certificates of conformity

- [KNX EIB-11/11700/14](#)