

CAT. N° 0 590 01



GREEN'UP PREMIUM PLASTIC SINGLE-PHASE CHARGING STATION - IP44 - IK08 - MODE 3 - 7.4 KW - 32 A - FOR 1 **VEHICLE**

Pack (number of units)	1
Volume (dm³)	20,4
Weight (g)	3 765,00

Product characteristics

Plastic single-phase charging stations - Mode 3

- Wall mounting charging stations to be equipped with pedestal Cat.No 0 590 52 for fixing to the ground

7.4 kW - 32 A

■ For charging 1 vehicle

General characteristics

Green'up™ Premium charging stations - for electric vehicle charging

- For charging all electric vehicles (equipped with single-phase and three-phase chargers) and plug-in hybrids in Mode 2 or Mode 3 in complete safety. Compliant with standards IEC 61851-1 and 61851-22.
- Charging station power can be adjusted with adapted protection devices and power supply circuits. Local wireless communication via embedded Bluetooth for configuration and control of charging station via smartphone or tablet using the IOS or Android compatible app.
- Available functions: changing station status, daily charging program, charging station activation/deactivation, power management, firmware updates
- Application additional functions: weekly changing program, consumption monitoring with cloud storage for data, status notification
- Remote wireless IP communication with communication kit Cat.No 0 590 56
- Equipped with:
- a 2P+E socket with Green'up Access safety shutter featuring the innovative Green'up system, a Legrand Group technology which activates "maximum power" mode, ensuring fast, safe charging for 2P+E plugs (Mode 2)
- a 3P+N+E (T2S) Type 2 socket with blanking plates (singlephase or three-phase operation) with pilot wire (Mode 3).
- \blacksquare Connected and protected from the electrical panel via 1 protected dedicated line (2 dedicated lines for 2-vehicle charging station).
- Off-peak control option via contactor, clock and switch (voltfree contact input 12 V=).
- Remote ON/OFF control option (volt-free contact input 12 V=).


Documentation

Catalogue pages & additional information

- Selection chart (p.372)
- Description page (p.374)
- Technical page (p.377)
- <u>Technical page (p.378-379)</u>

Installation instructions & related documents

- <u>LE09745AA-08</u>
- PIEC DETA-LE10645 AA-04






CAT. N° 0 590 01

- Installation & technical data
 - MODBUS TABLE GREEN-UP 059000-01-05-06_058000-01 V1
- Environmental product profile
 - LGRP-00676-V01

^{*} All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018





CAT. N° 0 590 01

Spare parts

CAT. NO.	DESCRIPTION	UNIT PRICE	MINIMUM ORDER QUANTITY
980949	COVER LED SOCKET T2 S		1
980951	SOCKET T2 S		1
980960	SUBSET LOCKING SYSTEM MODE 3		1

Spare Parts Guarantee

Does not affect the guarantee for the finished product.

Spare parts guaranteed against defects if exchanged within 2 weeks.

^{*} All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018