

CAT. N° 0 778 26



AUTOMATIC SWITCH SOLIROC WITHOUT NEUTRAL - 2-WIRE - IP55 IK10

Pack (number of units)	1
Volume (dm ³)	0,677
Weight (g)	203,00

Product characteristics

Automatic switches - IK 10 - IP 55

- Infrared detection
- Detection distance: 8 m
- Detection angle: 120°
- Light level threshold: 5 to 1275 lux
- Adjustable time delay: 10 s to 10 min
- Should preferably be installed in box depth 50 mm

Without neutral, 2-wire

- For installation in place of a 1-gang switch, with no additional wiring
- For controlling lamps :
 - LEDs: 3 to 100 W
 - compact fluorescent: 3 to 100 W
 - LEDs, CFLs, halogen, fluorescent tube with ferromagnetic or electronic ballast: 3 to 250 V~
 - 230 V halogen, incandescent lamps: 3 to 250 W
- Option of connecting up to 3 automatic switches in parallel
- For LED and compact fluorescent lamps, if several automatic switches are installed on the same circuit, the minimum load increases
- Consumption on standby: 0.02 W

General characteristics

Soliroc™ - control mechanisms IK 10

- Suitable for public buildings, unsupervised passageways, car parks, communal areas in buildings
- High resistance to IK 10 impacts and humidity
- 4 fixing points by plugging the plate directly on the wall and 4 blanking plates to be force-mounted on the plate (can only be removed by drilling)
- Mechanisms supplied with cover plates, to be equipped with support frames and plates

Documentation

Catalogue pages & additional information

- [Description page \(p.610\)](#)

Installation & technical data

- [F00996EN-04](#)

Installation instructions & related documents

- [LE01210AE](#)