

CAT. N° 0 778 96

**REPLACEMENT BLANKING PLUG SOLIROC - REMOVED ONLY BY DRILLING - SET OF 4**

| | |
|---------------------------|-------|
| Pack (number of units) | 5 |
| Volume (dm ³) | 0,14 |
| Weight (g) | 60,00 |

Product characteristics**Accessories**

- Cannot be used for Cat.Nos 0 778 74/75
- Supplied with 4 blanking plugs
- Take ISO 20 protective conductors

Replacement blanking plugs

- Can only be removed by drilling
- Set of 4

General characteristics**Soliroc™ - sockets and mounting accessories IK 10**

- Suitable for public buildings, unsupervised passageways, car parks, communal areas in buildings
- High resistance to IK 10 impacts and humidity
- 4 fixing points by plugging the plate directly on the wall and 4 blanking plates to be force-mounted on the plate (can only be removed by drilling)
- Mechanisms supplied complete with cover plates

Documentation**Catalogue pages & additional information**

- [Description page \(p.612\)](#)
- [Technical page \(p.616-617\)](#)

**Agreements & certificates of conformity**

- [NF-NF012_1023](#)
- [NF-NF012_1362](#)
- [OC / CB-569889/A1](#)
- [OC / CB-FR_701873](#)
- [OC / CB-619737](#)