

CAT. N° 3 106 69



EMPTY BATTERY CABINET FOR CAT.NO 310177/78

Pack (number of units)	1
Volume (dm ³)	129,718
Weight (g)	16 000,00

Product characteristics

Battery cabinet (empty)

- Battery cabinet for Cat.Nos 3 101 77/78

General characteristics

DAKER DK PLUS - On-line double conversion UPS (rack/tower) - single phase and three phase VFI

- The main parameters of the UPS, including the battery charge level and faults, are displayed on the LCD screen on the front panel
- The integrated communication software not only controls the UPS and its switch-off if there is a malfunction, and enables the user to test the main functions remotely, communicate via SNMP/Internet/network adaptor and access the functions of the UPS via the Internet, but can also send the user an SMS if specific events occur
- The internal extension connector enables aWEB/SNMP card or a relay interface to be installed which provides insulated contacts for applications on industrial control panels or remote alarm panels
- If there is an electronic fault, overload, overheating or for scheduled maintenance operations, the automatic or manual (optional) bypass ensures continuity of the power supply for critical loads. A bypass switch is available for maintenance

Documentation



Catalogue pages & additional information

- [Description page \(p.707\)](#)
- [Technical page \(p.708\)](#)
- [DAKER DK PLUS](#)