

CAT. N° 3 372 14



**XL³ S 160 SURFACE-MOUNTING 36-MODULES PER ROW
CABINET - RAL 9003 - 4 ROWS - 144 MODULES -
740X810X135 MM**

Pack (number of units)	1
Volume (dm³)	110,12
Weight (g)	18 372,00

Product characteristics

Surface mounting 36-module per row cabinets

- Faceplates and body: RAL 9003
- Number of rows : 4
- Number of modules : 144
- Height : 740 mm
- Width : 810 mm
- Depth : 135 mm

General characteristics

XL³ S 160 - 36 modules per row - "ready to use" metal distribution cabinets

- Cabinets supplied with rails fitted (150 mm fixing centres) and full height faceplates
- Doors and terminal blocks to be ordered separately
- Take DPX³ 160 and modular protection devices
- Used to create assemblies certified IEC 61439-2 and -3
- IP 40 with door
- IP 30 without door
- Cut-outs in top and bottom for feeding cables through
- Can take Lina 25 ducting

Documentation

Catalogue pages & additional information

- [Description page \(p.227\)](#)
- [Technical page \(p.229\)](#)

Agreements & certificates of conformity

- [LOVAG-IT 18](#)
- [LOVAG-IT 17](#)
- [LOVAG-IT 17](#)
- [LOVAG-IT 18](#)

Installation & technical data

- [F02368EN-02](#)

Environmental product profile

- [LGRP-00470-V01](#)