

CAT. N° 3 372 35



XL³ S 160 FLUSH-MOUNTING 36-MODULES PER ROW CABINET WITH FIXING LUGS - RAL 9003 - 5 ROWS - 180 MODULES - 962X883X138 MM

Pack (number of units)	1
Volume (dm ³)	128,352
Weight (g)	24 786,00

Product characteristics

Flush-mounting 36-module per row cabinets

- Supplied with fixing lugs
- Faceplates: RAL 9003
- Number of rows : 5
- Number of modules : 180
- Height : 962 mm
- Width : 883 mm
- Depth : 138 mm

General characteristics

XL³ S 160 - 36 modules per row - "ready to use" metal distribution cabinets

- Cabinets supplied with rails fitted (150 mm fixing centres) and full height faceplates
- Doors and terminal blocks to be ordered separately
- Take DPX³ 160 and modular protection devices
- Used to create assemblies certified IEC 61439-2 and -3
- IP 40 with door
- IP 30 without door
- Cut-outs in top and bottom for feeding cables through
- Can take Lina 25 ducting

Documentation

Catalogue pages & additional information

- [Description page \(p.227\)](#)
- [Technical page \(p.229\)](#)

Agreements & certificates of conformity

- [LOVAG-IT 18](#)
- [LOVAG-IT 17](#)
- [LOVAG-IT 17](#)
- [LOVAG-IT 18](#)

Installation & technical data

- [F02368EN-02](#)

Environmental product profile

- [LGRP-00470-V01](#)