

CAT. N° 3 375 71



XL³ S 630 DISTRIBUTION ENCLOSURES WITH 16 MODULES WIDE - TOTAL 1574X454X249 MM AND USABLE 1500X350X249 MM

Pack (number of units)	1
Volume (dm ³)	194,4
Weight (g)	27 102,00

Product characteristics

Enclosures

16 modules wide

- Faceplates: RAL 9003
- Body: RAL 7016
- Height total : 1574 mm
- Height faceplate : 1500 mm
- Width total : 454 mm
- Width usable : 350 mm
- Depth : 249 mm

General characteristics

XL³ S 630 - distribution enclosures

- Enclosures equipped with functional uprights and supplied with fixing supports for faceplates (fixing accessories for faceplates to be ordered separately)
- Doors and side panels to be ordered separately
- Take protection devices up to 630 A
- Used to create assemblies certified IEC 61439-2
- IP 40 with door
- IP 30 without door
- Removable, separable top and bottom panels
- Can take Lina 25 ducting and IP 55 Cabstop cable gland plates

Documentation

Catalogue pages & additional information

- [Description page \(p.234\)](#)
- [Technical page \(p.254\)](#)

Agreements & certificates of conformity

- [LOVAG-IT 17](#)
- [LOVAG-IT 18](#)
- [LOVAG-IT 18](#)
- [LOVAG-IT 18](#)
- [LOVAG-IT 18](#)

Installation & technical data

- [F02369EN-01](#)

Environmental product profile

- [LGRP-00471-V01](#)