

# CAT. N° 4 125 51



# POWER CONTACTOR CX<sup>3</sup> - WITH 230 V~ COLL AND HANDLE - 4P 400 V~ - 25 A

Pack (number of units)	2
Volume (dm³)	0,701
Weight (g)	452,00

# Product characteristics

#### Power contactors with 230 V~ coil and handle

- Manual override for test and repair function, carried out via the handle
- Permanent "ON" or "OFF" without automatic closing of the contactor

# 4-pole - 400 V~ ■ I max : 25 A

■ Type of contact : 4 N/O ■ Number of modules : 2

# General characteristics

#### Power contactors with handle CX3 - from 16 A to 63 A

- Conform to IEC/EN 61095
- Space for power supply busbar on top (up to 25 A)

# Documentation

# Catalogue pages & additional information

- Description page (p.086)
- Technical page (p.088)
- <u>Dimensions of din-rail equipment</u>

# Agreements & certificates of conformity

- NF-NF012\_2632
- <u>VDE-40029913</u>
- OC / CB-CB FR\_709436

# Installation & technical data

■ F01332EN-03

# Environmental product profile

- Environnemental product sheet n°8 E0008B-FR
- LGRP-2015-303-v1-EN

<sup>\*</sup> All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis: before-tax price list, May 2018