

## MODLINK MSDD DATA INSERT

1×SUB-D9fem./fem.+1×SUB-D9male/male+1×RJ45+1×USB-A

RJ45; USB; SUB-D9 GC; SUB-D9 GC

1 × RJ45, 8-pole metal, CAT5e (female/female)

1 × USB (female/female) form A

1 × SUB-D9 GC (female/female)

1 × SUB-D9 GC (male/male)

### [Link to Product](#)

#### Illustration



Product may differ from Image

#### General data

Dimensions H × W × D 88×51×45 mm

#### USB

Operating voltage 48 V AC/DC

Operating voltage (UL Rating) 42.4 V DC

Operating current max. 500 mA

Locking of ports Snap In

Specification USB: 2.0 (max. 480 Mbit/s)

#### SUB-D9

Operating voltage 48 V AC/DC

Operating voltage (UL Rating) max. 30 V AC/42.4 V DC

Operating current 3 A

Operating current (UL Rating) max. 175 mA

No. of poles 9-pole

Connection front side	SUB-D (female)
Connection rear side	SUB-D (female)
Locking of ports	UNC 4...40 bolt

**RJ45**

Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current (UL Rating)	max. 175 mA
Connection front side	RJ45
Connection rear side	RJ45
Locking of ports	Snap In
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)

**Commercial data**

country of origin	DE
customs tariff number	85366990
EAN	4048879037662
eClass	27189217
Packaging unit	1