

## MTL 1-PHASE CONTROL AND ISOLATION TRANSFORMER


P: 40VA IN: 230/400VAC +/- 15VAC OUT: 2x115VAC

40 VA

Isolation class T 60/B

### [Link to Product](#)

#### Illustration



Product may differ from Image

#### Approvals



### Input

Input voltage	230/400 ±15 V AC
Frequency	50...60 Hz
Input current	0.27 A (230 V AC); 0.15 A (400 V AC)
Inrush current	3 A (230 V AC); 1.73 A (400 V AC)
Short-circuit current	3.57 A (230 V AC); 2.06 A (400 V AC)

### Technical Data

LED display	LED (green) for input voltage
-------------	-------------------------------

### General data

Test isolation voltage	4 kV (prim./sec.)
Standards	EN 61558-1, EN 61558-2-4, EN 62041 category 0
Drill hole Ø	5.5×9 mm
Mounting method	DIN-rail mountable TH35-15 (EN 60715) or for key-hole mounting
Fixing centers a × b × c	96×60×5.5 mm
Dimensions H × W × D	108×87×104 mm
Temperature range	-20...+60 °C, no condensation

### Output

Output voltage	1 × 230, 1 × 115, 2 × 115 V AC
Output rating	40 VA

### Commercial data

country of origin	CZ
customs tariff number	85043180
EAN	4048879078221
eClass	27031302
Packaging unit	1