

S-Lamp 22 L M12(4)

Lamp

S-Lamp 22 L M12(4)

Lamp

Connection M12 (4-pin)

[Link al prodotto](#)**Immagine**

Immagine rappresentativa

**Mechanical protection**

UL Enclosure Type Rating (Front side) type 4X

Dati elettrici

Corrente di cortocircuito	1000 A
Kind of short circuit protective device	fuse 250 V / 0.1 A / 1.5 kA gG quick
Operating voltage of the luminous element	20...28 V
Picco di tensione nominale	800 V
Tensione di isolamento nominale	250 V
Corrente d'esercizio	12 mA (24 V DC)

caratteristiche ambientali

Salt-spray resistance	IEC 60068-2-11
Altitudine di installazione max.	≤ 2000 m
Umidità relativa	≤ 93% @ 40 °C
temperatura di stoccaggio	-40...90 °C
temperatura di esercizio	-25...70 °C

Mechanical data

Grid min.	30 mm
Mounting hole	22,3 mm
Mounting depth	30,2 mm
Dimensioni H×L×P	29,8 x 40 mm
Terminal	M12, 4 poli, A-code

Fixing	Threaded ring
Custodia	Plastica
Product article number of manufacturer	69065
Degree of protection (IP, EN 60529, front side)	IP66, IP67, IP69
Degree of protection (IP, EN 60529, rear side)	IP66, IP67
Alimentazione	
Rated operating current I _e	0,01 A
Mechanical data	
Installation height	9,8 mm
Mechanical data	
Can be illuminated	si
Collar shape	round
Color	nero
Collar color	nero
Color of illuminant	bianco
Type of the lamps	LED